




TOLI Carpet Tile

## MOROCA LINE <GX-4550V>



GX4551V

Technical Specifications	
<b>Product Description</b>	Nylon Tufted Carpet Tile
<b>Surface</b>	BCF Nylon100%
<b>Dyeing Method</b>	Solution Dyed
<b>Stain Protection</b>	Stain Release (Antifouling Finished)
<b>Base Fabric</b>	Nonwoven Polyester
<b>Backing</b>	PVC and Glass Fiber
<b>Size</b>	500mm x 500mm x 9.3mm
<b>Pile Height</b>	H6.0mm to L3.0mm (textured loop pile)
<b>Gauge &amp; Stitches</b>	1/10 <sup>th</sup> gauge 20.0 stitches/inch
<b>Yarn Weight</b>	25.7 oz/sq.yd
<b>Packing &amp; Net Weight</b>	16pcs/box=4m <sup>2</sup> /box (16.5kg/box)
<b>Origin</b>	Made in Japan
Performance Testing	
<b>Antistatic Property</b>	Less than 1.0kv (JIS L 1021-16, at 23 degrees C, 25%RH)
<b>Electrostatic Propensity</b>	Maximum Average 0.2kv (AATCC 134)
<b>Critical Radlant Flux</b>	Class 2 Average CRF 0.22/cm2 or higher (ASTM E648)
<b>Smoke Density</b>	Less than 450 (ASTM E662)
<b>Surface Flammability</b>	Passes DOC FF 1-70 (ASTM D2859)
<b>Flame-retardant Property</b>	Fire Defense Law in Japan Authorized No. E2190078
<b>Abrasion Resistance by Hexapod Tumble Drum Tester</b>	Appearance Rating 4.0 / Color Change Rating 4.0 (ASTM D5252)
<b>Tuft Bind</b>	7.0 Lbs. (ASTM D1335)
<b>Colorfastness to Light</b>	Rating 5.0 = No Change (AATCC 16)
Way of Installation	
 quarter turn	 monolithic
<b>Environmental Certificate</b>	
<b>CRI Green Label Plus</b>	GLP9977
<b>Product Notes</b>	
<p>Specifications are subject to nominal manufacturing variances.            Material supply and/or manufacturing processes may necessitate changes without notice.            Colors may vary slightly from dye lot to dye lot.            The use of chair pads under roller caster chairs may be required in order to maintain sufficient performance of the product.</p>	

TOLI Corporation - Global Department

2-10-4 Higashi-Shinbashi Minato-ku Tokyo 105-0021 Japan

Phone: 813-5403-2078 Fax: 813-5472-6307