



TOLI Carpet Tile

NOCTURE <GX-8400>



GX8401

Technical Specifications	
Product Description	Nylon Tufted Carpet Tile
Surface	BCF Nylon100%
Dyeing Method	Solution Dyed
Stain Protection	Stain Release (Antifouling Finished)
Base Fabric	Nonwoven Polyester
Backing	PVC and Glass Fiber
Size	500mm x 500mm x 8.5mm
Pile Height	H6.0mm/L4.5mm (cut and loop pile)
Gauge & Stitches	1/10 th gauge 12.0 stitches/inch
Yarn Weight	29.5 oz/sq.yd
Packing & Net Weight	16pcs/box=4m ² /box (20.2kg/box)
Origin	Made in Japan
Performance Testing	
Antistatic Property	Less than 1.0kv (JIS L 1021-16, at 23 degrees C, 25%RH)
Electrostatic Propensity	Maximum Average 1.8kv (AATCC 134)
Critical Radlant Flux	Class 1 Average CRF 0.45/cm2 or higher (ASTM E648)
Smoke Density	Less than 450 (ASTM E662)
Surface Flammability	Passes DOC FF 1-70 (ASTM D2859)
Flame-retardant Property	Fire Defense Law in Japan Authorized No. E2150032
Dimensional Stability	Less than 0.1% change (ASTM D7570)
Abrasion Resistance by Hexapod Tumble Drum Tester	Appearance Rating 3.0 / Color Change Rating 2.0 (ASTM D5252)
Tuft Bind	11.6 Lbs. (ASTM D1335)
Delamination Strength	4.2 Lbs/Inch (ASTM D3936)
Colorfastness to Light	Rating 5.0 = No Change (AATCC 16)
Way of Installation	
 quarter turn	 monolithic
Environmental Certificate	
CRI Green Label Plus	GLP9977
Product Notes	
Specifications are subject to nominal manufacturing variances. supply and/or manufacturing processes may necessitate changes without notice. vary slightly from dye lot to dye lot. pads under roller caster chairs may be required in order to maintain sufficient performance of the product.	
Material Colors may The use of chair	