





TOLI Carpet Tile

VENICHE <GX-9150V>



GX9153V

Technical Specifications	
Product Description	Nylon Tufted Carpet Tile
Surface	BCF Nylon100%
Dyeing Method	Solution Dyed
Stain Protection	Stain Release (Antifouling Finished)
Base Fabric	Nonwoven Polyester
Backing	PVC and Glass Fiber
Size	250mm x 1000mm x 8.3mm
Pile Height	H 5.5mm to L 3.0mm (textured loop pile)
Gauge & Stitches	1/10 th gauge 11.0 stitches/inch
Yarn Weight	20.1 oz/sq.yd
Packing & Net Weight	12pcs/box=3m ² /box (16.0kg/box)
Origin	Made in Japan
Performance Testing	
Antistatic Property	Less than 1.0kv (JIS L 1021-16, at 23 degrees C, 25%RH)
Electrostatic Propensity	Maximum Average 3.1kv (AATCC 134)
Critical Radlant Flux	Class 1 Average CRF 0.45/cm2 or higher (ASTM E648)
Smoke Density	Less than 450 (ASTM E662)
Surface Flammability	Passes DOC FF 1-70 (ASTM D2859)
Flame-retardant Property	Fire Defense Law in Japan Authorized No. E2150035
Dimensional Stability	Less than 0.1% change (ASTM D7570)
Abrasion Resistance by Hexapod Tumble Drum Tester	Appearance Rating 3.5 / Color Change Rating 3.5 (ASTM D5252)
Tuft Bind	10.3 Lbs. (ASTM D1335)
Delamination Strength	5.4 Lbs/Inch (ASTM D3936)
Colorfastness to Light	Rating 5.0 = No Change (AATCC 16)
Way of Installation	
 ashlar	 monolithic
Environmental Certificate	
CRI Green Label Plus	GLP9977
Product Notes	
<p>Specifications are subject to nominal manufacturing variances. supply and/or manufacturing processes may necessitate changes without notice. vary slightly from dye lot to dye lot.</p> <p>The use of chair pads under roller caster chairs may be required in order to maintain sufficient performance of the product.</p>	
<p>Material Colors may</p>	