






TOLI Carpet Tile

ROCK GARDEN <GX-9250V>

 <p>GX9251V</p>	Technical Specifications	
	Product Description	Nylon Tufted Carpet Tile
	Surface	BCF Nylon100%
	Dyeing Method	Solution Dyed
	Stain Protection	Stain Release (Antifouling Finished)
	Base Fabric	Nonwoven Polyester
	Backing	PVC and Glass Fiber
	Size	250mm x 1000mm x 9.3mm
	Pile Height	H 8.0mm to L 3.0mm (textured loop pile)
	Gauge & Stitches	1/10 th gauge 14.0 stitches/inch
	Yarn Weight	20.1 oz/sq.yd
	Packing & Net Weight	12pcs/box=3m ² /box (17.0kg/box)
	Origin	Made in Japan
	Performance Testing	
	Antistatic Property	Less than 1.0kv (JIS L 1021-16, at 23 degrees C, 25%RH)
	Electrostatic Propensity	Maximum Average 1.6kv (AATCC 134)
	Critical Radlant Flux	Class 2 Average CRF 0.22/cm2 or higher (ASTM E648)
	Smoke Density	Less than 450 (ASTM E662)
	Surface Flammability	Passes DOC FF 1-70 (ASTM D2859)
	Flame-retardant Property	Fire Defense Law in Japan Authorized No. E2180254
	Dimensional Stability	Less than 0.1% change (ASTM D7570)
	Abrasion Resistance by Hexapod Tumble Drum Tester	Appearance Rating 4.0 / Color Change Rating 4.5 (ASTM D5252)
	Tuft Bind	10.2 Lbs. (ASTM D1335)
	Delamination Strength	5.2 Lbs/Inch (ASTM D3936)
	Colorfastness to Light	Rating 5.0 = No Change (AATCC 16)
Way of Installation		
 ashlar	 monolithic	
Environmental Certificate		
CRI Green Label Plus	GLP9977	
Product Notes		
<p>Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice. Colors may vary slightly from dye lot to dye lot. The use of chair pads under roller caster chairs may be required in order to maintain sufficient performance of the product.</p>		

TOLI Corporation - Global Department
2-10-4 Higashi-Shinbashi Minato-ku Tokyo 105-0021 Japan
Phone: 813-5403-2078 Fax: 813-5472-6307